



## MRV 600 Roof Vent

### One-Way Moisture Relief Vent

**Description:**

The MRV 600 Roof Vent is engineered to prolong the life of the roof system by reducing moisture within the roof system and trapped air pressure within the building. Trapped air pressure and moisture can cause a reduction in thermal protection of the insulation and roof membrane system leading to roof deck damage. The vandal-proof cap design provides security while preventing entry of wind-blown rain or snow.

**Packaging:**

25 Roof Vents per Box

**Application:**

Recommended spacing is a minimum of one vent every 500 square feet. Cut a 4" diameter opening through the membrane and insulation material, remove material to vapor barrier or deck, lay vent on top of roof membrane and attach vent to the roof deck with the appropriate fastener. Install 4 fasteners per vent, evenly spaced. Clean area of vent that is to receive flashing material with clean rag and solvent to remove oil film from vent. Flash in vent with one of the two following procedures:

- Apply a 3 course coating and fabric utilizing the PM PF200 Polyester Fabric and PM Silicone Coating.
  - Apply 12 to 15 mils of silicone coating over surface to receive fabric.
  - Embed fabric into silicone coating while still wet. Fabric should extend at least 2" on to the flange of the vent and at least 4" on to the roof surface.
  - After the base coating has cured, apply a generous coat of silicone coating over the fabric to ensure complete saturation.
- Apply PM FT500 Self-Sealing Butyl Fleece Tape.
  - Install fleece tape a minimum of 2" on to the flange of the vent and extending at least 2" on to the roof surface per the application guidelines on the FT500 Technical Product Data sheet.
  - Apply a generous coat of PM Silicone Coating to the surface of the fleece tape. Ensure coating is applied generously to ensure a good seal over the fleece surface.

NOTE: If the roof system has an existing silicone coating, only flash in vent with the first option above as the butyl fleece tape will not adhere to the silicone coating.

### Physical Properties

Dimensions:	Height.....8"	Breather Vent:	Holes.....8
	Base Diameter .....11"		Hole Diameter.....½"
	Stack Diameter at Base.....5"	Vent Cap:	Diameter.....4"
Material Type:	Base/Stack/Cap.....051 Aluminum	Package Info:	Vents/Box.....25
	Valve.....Duro Nitrile		Weight/Box.....22 lbs.

*The information reported herein are based upon information reasonably available to Progressive Materials, LLC at the time publication, and are presented in good faith but are not to be construed as warranties or guarantees, expressed or implied. We warrant that our products will meet our written specifications. We make no other warranty of merchantability of fitness for a particular purpose. Our total liability and customers' exclusive remedy for all proven claims is replacement of nonconforming product and in no event shall we be liable for any other damages, including without limitation to special, incidental, punitive, or consequential damages.*