

Pro-Grip PG 750 Non-Slip Walkway Granules

Safety Yellow Walkway Granules

Description:

Pro-Grip PG 750 Non-Slip Walkway Granules were designed to enhance the impact resistance of the roof surface and also provide a non-skid walking surface when embedded in Pro-Grip PG 700 100% Silicone Yellow Walkway Coating. Pro-Grip PG 750 Non-Slip Walkway Granules were designed to provide high-performance UV resistance for outdoor applications. Only the most UV stable pigments have been incorporated into the product to maintain colorfastness.

Packaging:

Packaged in two (2) gallon pails containing 25 lbs. of product.
 Sixty (60) pails per pallet.

Storage and Shelf Life:

Pro-Grip PG 750 Non-Slip Walkway Granules have a recommended shelf life of five (5) years when stored in dry environments.

Application:

Immediately after the application of PG 700 Walkway Coating, evenly broadcast the Pro-Grip PG 750 Non-Slip Walkway Granules into the wet coating. The recommended application rate is as follows:

- Walkway Areas – 25 mils (1.65gal/sq.) of Walkway Coating with 40 lbs./sq. of Walkway Granules.
- Impact Resistant Areas – 40 mils (2.65 gal/sq.) of Walkway Coating with 60 lbs./sq. of Walkway Granules.

IMPORTANT: The Walkway Granules will settle into the Walkway Coating. Apply the granules generously and, within a few minutes, inspect the surface and re-apply as needed to obtain a continuous film of granules.

Clean-up:

After the coating has completely cured, usually the next day, remove all loose granules from the surface. For best results, use a small hand blower and a soft-bristled push broom.

General Data & Properties

Hardness (Moh’s Hardness Scale).....	6.5-7.0	<u>Composition</u>	
Bulk Density (ASTM C29/C29M-97).....	90-100 Lbs./Cu. Ft.	Silica Sand.....	97.5%
Specific Gravity (ASTM C128-01e1).....	2.65	Resin.....	2.0%
		Colorants.....	0.5%

The information reported herein are based upon information reasonably available to Progressive Materials, LLC at the time publication, and are presented in good faith but are not to be construed as warranties or guarantees, expressed or implied. We warrant that our products will meet our written specifications. We make no other warranty of merchantability of fitness for a particular purpose. Our total liability and customers’ exclusive remedy for all proven claims is replacement of nonconforming product and in no event shall we be liable for any other damages, including without limitation to special, incidental, punitive, or consequential damages.