

# FG-400 Flashing Grade Silicone

Prepared to U.S. OSHA, CMA, ANSI, Canadian WHMIS, Australian WorkSafe, Japanese Industrial Standard JIS Z 7250:2000, and European Union REACH Regulations

# **SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME: FG-400 Flashing Grade Silicone

CHEMICAL FAMILY NAME: Silicone Sealant

U.N. NUMBER: None

U.N. DANGEROUS GOODS CLASS: Non-Regulated

SUPPLIER/MANUFACTURER'S NAME: Progressive Materials, LLC

ADDRESS: 540 Central Court, New Albany, IN 47150 USA

EMERGENCY PHONE: TOLL-FREE in USA/Canada - Chemtrec 1-800-424-9300
National Poison Control Center (U.S.) 1-800-222-1222

BUSINESS PHONE: 812-944-7803 (Product Information)

WEB SITE: <a href="https://www.pmsilicone.com">www.pmsilicone.com</a>
DATE OF CURRENT REVISION:
October 07, 2017
May 29, 2015

# **SECTION 2 - HAZARDS IDENTIFICATION**

### **EMERGENCY OVERVIEW:**

**Product Description:** This product is a white liquid with a mild odor.

**Health Hazards:** Exposure to the product may cause skin and eye irritation. Prolonged exposure may cause skin sensitization. Ingestion is not a normal route of exposure under normal product use. If swallowed, product may cause gastrointestinal irritation. This product contains an ingredient that is suspected of causing cancer and/or reproductive harm.

Flammability Hazards: This product is flammable with a flash point >200°F (>93.3°C).

Reactivity Hazards: None known.

**Environmental Hazards:** The environmental effects of this product have not been investigated; however it is expected to cause adverse effects in the environment.


**Emergency Considerations:** Emergency responders must wear the proper personal protective equipment (and have appropriate fire-suppression equipment) suitable for the situation to which they are responding.

**US DOT SYMBOLS** 

See Section 14 for Details

GHS Hazard Symbols





# GHS CLASSIFICATION OF SUBSTANCE OR MIXTURE IN ACCORDANCE WITH 29 CFR 1200 (OSHA HCS) AND THE EUROPEAN UNION DIRECTIVES:

This product does meet the definition of a hazardous substance or preparation as defined by 29 CFR 1910. 1200 AND the European Union Council Directives 67/548/EEC, 1999/45/EC, 1272/2008/EC and subsequent Directives.

# **EU HAZARD CLASSIFICATION OF INGREDIENTS:**

CAS# 70131-67-8 is not listed in ESIS

EC# 215-279-6 This substance is not classified in the Annex VI

EC# 613-156-5 This substance is not classified in the Annex VI

EC# 245-366-4 This substance is not classified in the Annex VI

EC# 236-675-5 This substance is not classified in the Annex VI

EC# 209-136-7 Annex VI Index# 014-018-00-1

EC# 601-216-3 This substance is not classified in the Annex VI

Component(s) Contributing to Classification(s)

2-Butanone, O, O', O"-(Methylsilylidyne) Trioxime, Titanium Dioxide, Octamethylcyclotetrasiloxane, Silicon Dioxide

October 2017 Page 1 of 8 <u>www.pmsilicone.com</u>



# FG-400 Flashing Grade Silicone

# GHS Hazard Classification(s):

Skin Irritation Category 2

Eye Irritation Category 2A

Skin Sensitization Category 1

Carcinogenicity Category 2

Reproductive Toxicity Category 2

Specific Target Organ Toxicity Category 3 (Respiratory Irritation)

Chronic Aquatic Toxicity Category 3

### Hazard Statement(s):

H315: Causes skin irritation

H319: Causes serious eye irritation

H317: May cause and allergic skin reaction

H351: Suspected of causing cancer

H361: Suspected of damaging fertility or the unborn child

H335: May cause respiratory irritation.

H412: Harmful to aquatic life with long lasting effects

# **Prevention Statement(s):**

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P272: Contaminated work clothing should not be allowed out of the workplace.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

### Response Statement(s):

P308+P313: IF exposed or concerned: Get medical advice/attention.

P302+P352: IF ON SKIN: Wash with plenty of water.

P321: Specific treatment (See Section 4 of this SDS).

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312: Call a POISON CENTER/doctor if you feel unwell.

### Storage Statement(s):

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

### Disposal Statement(s):

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

# **HEALTH HAZARDS OR RISKS FROM EXPOSURE:**

This product does not meet the criteria for PBT or vPvB in accordance with Annex XIII

**ACUTE:** This material may cause irritation to skin, eye, and respiratory system. May cause skin sensitization. Ingestion of this product may cause gastrointestinal irritation. This product contains an ingredient(s) that are suspected of causing reproductive harm.

CHRONIC: Prolonged or repeated skin contact may cause skin reactions.

TARGET ORGANS: ACUTE: Eye, Skin, Respiratory System CHRONIC: Respiratory System



# FG-400 Flashing Grade Silicone

# **SECTION 3 - COMPOSITION and INFORMATION ON INGREDIENTS**

HAZARDOUS INGREDIENTS:	CAS#	EINECS#	ICSC#	WT %	HAZARD CLASSIFICATION
Liquid Silicone Polymer	70131-67-8	Not Listed in ESIS	Not Listed	40 – 50%	NOT CLASSIFIED
Limestone	1317-65-3	215-279-6	Not Listed	25 – 35%	NOT CLASSIFIED
Polydimethylsiloxane	63148-62-9	613-156-5	Not Listed	5 – 15%	NOT CLASSIFIED
2-Butanone,O,O', O"- (Methylsilylidyne)Trioxime	22984-54-9	245-366-4	Not Listed	1 – 10%	SKIN IRRIT CAT 2, EYE IRRIT. CAT 2A, SKIN SENS CAT 1
Titanium Dioxide	13463-67-7	236-675-5	0338	1 – 10%	CARC. CAT 2
Octamethylcyclotetrasiloxane	556-67-2	209-136-7	0310	1 – 10%	REPR. CAT 2, AQUATIC CHRONIC CAT 2
Silicon Dioxide	112945-52-5	601-216-3	Not Listed	1 – 10%	SKIN IRRIT CAT 2, EYE IRRIT. CAT 2A, STOT SE CAT 3 (RESP IRRIT)
Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).					

# **SECTION 4 - FIRST-AID MEASURES**

**EYE CONTACT:** If product enters the eyes, open eyes while under gentle running water for at least 15 minutes. Seek medical attention if irritation develops.

**SKIN CONTACT:** Wash skin thoroughly after handling. Seek medical attention if irritation develops and persists. Remove contaminated clothing. Launder contaminated clothing before re-use.

**INHALATION:** If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention if breathing dificulty continues.

**INGESTION:** If product is swallowed, call physician or poison control center for most current information. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and/or MSDS with the victim to the health professional.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Pre-existing skin, or eye problems may be aggravated by exposure to this product.

**RECOMMENDATIONS TO PHYSICIANS:** Treat symptoms and reduce over-exposure.

### SECTION 5 - FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS (in air by volume, %): Lower (LEL): Not Established Upper (UEL):

FIRE EXTINGUISHING MATERIALS: Carbon dioxide, foam, dry chemical, halon, water spray, sand,

limestone powder.

UNUSUAL FIRE AND EXPLOSION HAZARDS: This material has been tested to ASTM D-4206 Standard and found

not to sustain combustion

<u>Explosion Sensitivity to Mechanical Impact</u>: Not Sensitive. <u>Explosion Sensitivity to Static Discharge</u>: Not Sensitive

SPECIAL FIRE-FIGHTING PROCEDURES: Incir

Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full

firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of

water, or other environmentally sensitive areas.



### NFPA RATING SYSTEM

# Health 2 0 Reactivity Other

# FG-400 Flashing Grade Silicone

# **HMIS RATING SYSTEM**

H.	HAZARDOUS MATERIAL IDENTIFICATION SYSTEM					
	HEALTH HAZARD (BLUE)					
	FLAMMABILITY HAZARD (RED) 1					
	PHYSICAL HAZARD (YELLOW)					
	PROTECTIVE EQUIPMENT					
	EYES RESPIRATORY HANDS BOI				DY	
	5	See Sect 8		See Sect 8		
	For Routine Industrial Use and Handling Applications					

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

# **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

**SPILL AND LEAK RESPONSE:** Personnel should be trained for spill response operations.

**SPILLS:** Contain spill if safe to do so. Prevent entry into drains, sewers, and other waterways. Soak up with a non-combustible absorbent material and place in an appropriate container for disposal. Dispose of in accordance with applicable Federal, State, and local procedures (see Section 13, Disposal Considerations).

## SECTION 7 - HANDLING and STORAGE

**WORK PRACTICES AND HYGIENE PRACTICES:** As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after handling this product. Do not eat, drink, smoke, or apply cosmetics while handling this product. Avoid breathing vapors/mists generated by this product. Use in a well-ventilated location. Remove contaminated clothing immediately.

STORAGE AND HANDLING PRACTICES: Keep container tightly closed and in a dry and cool place.

# **SECTION 8 - EXPOSURE CONTROLS - PERSONAL PROTECTION**

### **EXPOSURE LIMITS/GUIDELINES:**

Chemical Name	CAS#	ACGIH TWA	OSHA TWA	WEEL
Liquid Silicone Polymer	70131-67-8	Not Listed	Not Listed	Not Listed
Limestone	1317-65-3	10 mg/m³	15 mg/m³	10 mg/m³
Polydimethylsiloxane	63148-62-9	Not Listed	Not Listed	Not Listed
2-Butanone,O,O', O"- (Methylsilylidyne)Trioxime	22984-54-9	Not Listed	Not Listed	Not Listed
Titanium Dioxide	13463-67-7	10 mg/m³	10 mg/m³	10 mg/m³
Octamethylcyclotetrasiloxane	556-67-2	Not Listed	Not Listed	Not Listed
Silicon Dioxide	112945-52-5	6 mg/m³	10 mg/m³	3 mg/m³ Respirable dust

Currently, International exposure limits are not established for the components of this product. Please check with competent authority in each country for the most recent limits in place.



# FG-400 Flashing Grade Silicone

**VENTILATION AND ENGINEERING CONTROLS:** Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above. Use local exhaust ventilation to control airborne vapor. Ensure eyewash/safety shower stations are available near areas where this product is used.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada, or standards of EU member states (including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.

**RESPIRATORY PROTECTION:** Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

**EYE PROTECTION:** Safety glasses or chemical goggles as appropriate to prevent eye contact. If necessary, refer to U.S. OSHA 29 CFR 1910.133 or appropriate Canadian Standards.

**HAND PROTECTION:** Use chemical resistant gloves to prevent skin contact. If necessary, refer to U.S. OSHA 29 CFR 1910.138 or appropriate Standards of Canada.

**BODY PROTECTION:** Use body protection appropriate to prevent contact (e.g. lab coat, overalls). If necessary, refer to appropriate Standards of Canada, or appropriate Standards of the EU, Australian Standards, or relevant Japanese Standards.

# **SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES**

PHYSICAL STATE: Liquid

APPEARANCE & ODOR: White liquid with a mild odor

ODOR THRESHOLD (PPM):

FLASH POINT:

AUTOIGNITION TEMPERATURE:

VAPOR PRESSURE (mmHg):

VAPOR DENSITY:

Not Available

Not Available

Not Available

EVAPORATION RATE (nBuAc = 1): <1

BOILING POINT (C°):

FREEZING POINT (C°):

Not Available

### **SECTION 10 - STABILITY and REACTIVITY**

**STABILITY:** Product is stable

**DECOMPOSITION PRODUCTS:** When heated to decomposition this product produces noxious gases such as CO,

CO<sub>2</sub>, and others.

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: None known

**HAZARDOUS POLYMERIZATION:** Will not occur. **CONDITIONS TO AVOID:** Heat and sources of ignition.

# **SECTION 11 - TOXICOLOGICAL INFORMATION**

**TOXICITY DATA:** Toxicity data is available for this product:

CAS# 13463-67-7 LD50 Acute Oral >10000 mg/kg Rat CAS# 112945-52-5 LD50 Acute Oral 3160 mg/kg Rat CAS# 556-67-2 LD50 Inhalation >12.7 mg/kg/4Hr Rat CAS# 556-67-2 LD50 Acute Oral 1540 mg/kg Rat CAS# 556-67-2 LD50 Acute Dermal >2400 mg/kg Rat

October 2017 Page 5 of 8 <u>www.pmsilicone.com</u>



# FG-400 Flashing Grade Silicone

Acute toxicity	Based on available data, the classification criteria are not met
Skin corrosion / irritation	Skin Irritation Category 2
Serious eye damage / irritation	Eye Irritation Category 2A
Respiratory or skin sensitization	Skin Sensitization Category 1
Germ cell mutagenicity	Based on available data, the classification criteria are not met
Carcinogenicity	Carcinogenicity Category 2
Reproductive toxicity	Reproductive Category 2
STOT-single exposure	Specific Target Organ Toxicity – Single Exposure (Respiratory Irritation)
STOT-repeated exposure	Based on available data, the classification criteria are not met
Aspiration hazard	Based on available data, the classification criteria are not met

**SUSPECTED CANCER AGENT:** One or more of the ingredients are found on the following lists: FEDERAL OSHA Z LIST, NTP, CAL/OSHA, IARC and therefore are considered to be, or suspected to be a cancer-causing agent by these agencies.

Titanium dioxide (13463-67-7)

ACGIH: A4 – Not classifiable as a Human Carcinogen

NIOSH: Potential occupational carcinogen

IARC: Monograph 93 posted, Monograph 47 [1989] (Group 2B (possibly carcinogenic to humans))

**IRRITANCY OF PRODUCT:** Contact with this product can be irritating to exposed skin, eyes, and respiratory system.

**SENSITIZATION OF PRODUCT:** This product is considered a skin sensitizer.

REPRODUCTIVE TOXICITY INFORMATION: Octamethylcyclotetrasiloxane CAS# 556-67-2 is listed by the European

Chemical Commission as a reproductive hazard causing harmful effects to fertility or the unborn child.

SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE: None known SPECIFIC TARGET ORGAN TOXICITY – REPEATED EXPOSURE: None known

**ASPIRATION HAZARD: None** 

## **SECTION 12 - ECOLOGICAL INFORMATION**

## ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

**TOXICITY:** No specific data is currently available on this product's effects on aquatic life, however release of this product may have long term effects on the aquatic environment.

Specific Component Data:

Octamethylcyclotetrasiloxane (556-67-2)

**Test & Species Conditions** 

96 Hr LC50 Brachydanio rerio >500 mg/L

96 Hr LC50 Lepomis macrochirus >1000 mg/L

24 Hr EC50 Daphnia magna 25.2 mg/L

**PERSISTENCE AND DEGRADABILITY:** No specific data available on this product. **BIOACCUMULATIVE POTENTIAL:** No specific data available on this product.

MOBILITY IN SOIL: No specific data available on this product.

RESULTS OF PBT AND vPvB ASSESMENT: No specific data available on this product.

OTHER ADVERSE EFFECTS: No specific data available on this product.

WATER ENDANGERMENT CLASS: Not believed to be water endangering in accordance with EU Guideline 91/155-EWG.

At present there are no ecotoxicological assessments for this product.

# **SECTION 13 - DISPOSAL CONSIDERATIONS**

**PREPARING WASTES FOR DISPOSAL:** Waste disposal must be in accordance with appropriate Federal, State, and local regulations, those of Canada, Australia, EU Member States and Japan.

RCRA WASTE CODE: None listed EU WASTE CODE: Not Listed

October 2017 Page 6 of 8 <u>www.pmsilicone.com</u>



FG-400 Flashing Grade Silicone

# **SECTION 14 - TRANSPORTATION INFORMATION**

### US DOT; IATA; IMO; ADR:

THIS PRODUCT IS NOT CLASSIFIED AS DANGEROUS GOODS AS DEFINED BY 49 CFR 172.101 BY THE U.S. DEPARTMENT OF TRANSPORTATION.

PROPER SHIPPING NAME: Non-Regulated

**HAZARD CLASS NUMBER and DESCRIPTION: None** 

**UN IDENTIFICATION NUMBER: None** 

**PACKING GROUP: None** 

DOT LABEL(S) REQUIRED: None

NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER (2016): None

MARINE POLLUTANT: This product's ingredients that are not classified by the DOT as a Marine Pollutant (as defined by

49 CFR 172.101, Appendix B)

TRANSPORT CANADA, TRANSPORTATION OF DANGEROUS GOODS REGULATIONS:

This product is not classified as Dangerous Goods, per regulations of Transport Canada.

INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA):

This product is not classified as Dangerous Goods, by rules of IATA:

INTERNATIONAL MARITIME ORGANIZATION (IMO) DESIGNATION:

This product is not classified as Dangerous Goods by the International Maritime Organization.

EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD (ADR):

This product is not classified by the United Nations Economic Commission for Europe to be dangerous goods.

Harmonized Tariff Code Not Listed

# **SECTION 15 - REGULATORY INFORMATION**

### **UNITED STATES REGULATIONS**

**SARA REPORTING REQUIREMENTS:** This product is not subject to the reporting requirements of Sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act., as follows: None

TSCA: All components in this product are listed on the US Toxic Substances Control Act (TSCA) inventory of chemicals.

SARA 311/312:

Acute Health: Yes Chronic Yes Fire: No Reactivity: No

Health:

<u>U.S. SARA THRESHOLD PLANNING QUANTITY:</u> There are no specific Threshold Planning Quantities for this product. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) may apply, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ): None

# CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65):

**WARNING** This product contains Titanium Dioxide which is known to the State of California as a cancer hazard if in respirable form.

# **CANADIAN REGULATIONS:**

CANADIAN DSL/NDSL INVENTORY STATUS: All of the components of this product are on the DSL Inventory

**CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS:** No component of this product is on the CEPA First Priorities Substance Lists.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS: Classified per WHMIS 2015

### **EUROPEAN ECONOMIC COMMUNITY INFORMATION:**

# **EU LABELING AND CLASSIFICATION:**

Classification of the mixture according to Regulation (EC) No1272/2008. See section 2 for details.

# **AUSTRALIAN INFORMATION FOR PRODUCT:**

**AUSTRALIAN INVENTORY OF CHEMICAL SUBSTANCES (AICS) STATUS:** All components of this product are listed or exempt from listing on the AICS.

STANDARD FOR THE UNIFORM SCHEDULING OF DRUGS AND POISONS: Not applicable.

October 2017 Page 7 of 8 <u>www.pmsilicone.com</u>



# FG-400 Flashing Grade Silicone

# **JAPANESE INFORMATION FOR PRODUCT:**

**JAPAN INDUSTRIAL SAFETY AND HEALTH LAW:** This product has been classified per the Japan Industrial Safety and Health Law. See Section 2 for the GHS Classification.

### **INTERNATIONAL CHEMICAL INVENTORIES:**

Listing of the components on individual country Chemical Inventories is as follows:

Asia-Pac: Listed or exempt from listing

Australian Inventory of Chemical Substances (AICS): Listed or exempt from listing

Korean Existing Chemicals List (ECL): Listed or exempt from listing

Japanese Existing National Inventory of Chemical Substances (ENCS): Listed or exempt from listing Philippines Inventory if Chemicals and Chemical Substances (PICCS): Listed or exempt from listing

Swiss Giftliste List of Toxic Substances:

Listed or exempt from listing

U.S. TSCA: Listed

# **SECTION 16 - OTHER INFORMATION**

PREPARED BY: Chris Eigbrett

MSDS to GHS Compliance

www.msdstoghs.com

Disclaimer: The information and recommendations in this document are accurate to the best of our knowledge. User must conduct their own tests to determine the suitability of these products for their particular purposes. Because of numerous factors affecting results, Progressive Materials, LLC MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR PURPOSE, other than the material conforms to our applicable current specifications. Progressive Materials, LLC assumes no legal responsibility for use or reliance on the information contained in this Material Safety Data Sheet.

October 2017 Page 8 of 8 <u>www.pmsilicone.com</u>