

FT 500 Butyl Fleece Tape

Self-Sealing Tape

Technical Product Data

BASIC USES & DESCRIPTION:

FT 500 Butyl Fleece Tape is butyl rubber compound with an absorbent polyester fleece face. This product was developed to seal a variety surfaces and prevent moisture intrusion. It is ideal for applications over EDPM roofs. This product is extremely flexible and moldable which also makes it a great product for sealing curbs and other roof-top equipment.

PACKAGING:

FT 500 Butyl Fleece Tape is available in 4" x 65.5' rolls and contains 4 rolls per box.

STORAGE AND SHELF LIFE:

FT 500 Butyl Fleece Tape has a recommended shelf life of 24 months when stored flat in original packaging in cool, dry conditions. Refer to product packaging for manufacture date.

SURFACE PREPARATION:

All surfaces should be dry, smooth, clean and free from dirt, dust, carbon dust, loose paint or coatings, oil, grease, rust or other foreign matter. Treat the surface as directed below for the appropriate substrate:

- ▶ *EDPM Membranes – Clean with P-120 or a mild detergent and a scrub brush.*

APPLICATION:

Apply FT 500 Butyl Fleece Tape only in temperatures between 40° and 105° Fahrenheit. After the surface has been properly prepared, cut tape to desired length. Remove the release liner and position over desired area. Precisely apply the tape directly to the area on the first attempt as trying to remove may damage the tape and/or the roofing surface. Firmly press on all areas of tape with a finger or roller making sure tape stays conformed to the roof surface. Always roll from the center towards the outside to remove any air pockets. Edges must be free of any fishmouths. Do not stretch tape during application. Apply PM silicone coating over tape the same day.

The information reported herein are based upon information reasonably available to Progressive Materials, LLC at the time publication, and are presented in good faith but are not to be construed as warranties or guarantees, expressed or implied. We warrant that our products will meet our written specifications. We make no other warranty of merchantability of fitness for a particular purpose. Our total liability and customers' exclusive remedy for all proven claims is replacement of nonconforming product and in no event shall we be liable for any other damages, including without limitation to special, incidental, punitive, or consequential damages.

TYPICAL PROPERTIES

Test Properties	Value	Test Properties	Value
Appearance	Gray backing with a white fleece face	Dynamic Sheer Adhesion	17.4 lb/in ²
90° Peel Adhesion	11.6 lb/in ²	180° Peel Adhesion	13.1 lb/in ²
Specific Gravity	[.69 lb/in ²]	Moisture Vapor Transmission Rate	[.25 lb/in ² /24hr]
Application Temperature Range	40° to 105° F	Service Temperature Range	-40° to 194°F

Contact Progressive Materials for more detailed specifications on our roofing systems and to find a certified contractor near you.

Revision Date: July 22, 2026