



Technical Product Data

P-160 Bleed Block Primer

BASIC USES & DESCRIPTION:

P-160 is a high quality, plasticizer free, single component, water based, acrylic primer. P-160 is designed for application over smooth asphalt roof surfaces to enhance adhesion of silicone roof coatings. P-160 is formulated to act as a barrier between the asphalt surface and the silicone roof coating to prevent yellowing of the coating due to chemicals bleeding out of the asphalt roof. P-160 can be applied with spray, brush, or roller. Spray application is preferred method.

LIMITATIONS & PRECAUTIONS:

Surface must be clean and dry. P-160 is water based and requires evaporation to cure. Material must cure for at least 24 hours. Low temperature and high humidity will slow the cure process. In these situations, even longer cure times will be necessary. Note: Blistering will occur if top coat is applied over base coat that is not completely dry. Do not apply P-160 Bleed-Block Primer if there is any moisture on the substrate or risk of precipitation. contact Progressive Materials. Product should not be applied when the ambient temperature is below 32°F or the temperate will fall to within 5 degrees of the dew point within 6 hours after application. Apply P-160 at a rate of 1 gallon per 100 square feet.

STORAGE AND SHELF LIFE:

P-160 is water based and is not freeze-thaw stable. P-160 should be stored between 40°F and 70°F. Shelf life is 12 months from manufacture date.

PACKAGING SIZES:

P-160 Bleed Block Primer is available in 5 gallon and 55 gallon containers.

APPLICATION:

P-160 may be brushed, rolled, or sprayed on a clean, dry surface. Spray application is preferred. For equipment specifications,

TYPICAL PROPERTIES

As Supplied:			
Appearance:	Tan	Clean Up	Water
Total Solids (volume):	50% +/- 2%	Shelf Life	12 Months
Weight Per Gallon	11.4 lbs. per gallon +/- 0.2	Viscosity	100 +/- 15 cP
VOC:	<50 grams/liter		

The information reported herein are based upon information reasonably available to Progressive Materials, LLC at the time publication, and are presented in good faith but are not to be construed as warranties or guarantees, expressed or implied.

Contact Progressive Materials for more detailed specifications on our roofing systems and to find a certified contractor near you.



Revision Date: November 10, 2016

PROGRESSIVE MATERIALS 540 CENTRAL COURT • NEW ALBANY, IN 47150 PHONE (812) 944-7803 FAX (812) 944-7804 WEB PMsilicone.com

